## MATERIAL SAFETY DATA SHEET

(Similar to Form OSHA-20)

SECTION I				
MANUFACTURER'S NAME CHAMPION'S CHOICE, INC.	EMERGENCY TELEPHONE NO. 714/635-4491			
ADDRESS (Number Street City State and Zip Code) 1910 E. VIA BURTON, ANAHEIM, CALIFORNIA 92806				
CHEMICAL NAME AND SYNONYMS	TRADE NAME AND SYNONYMS PETROCHEM MICROFINISH DOM 5508			
CHEMICAL FAMILY FORMU	LA			

		(Units)		++	(Units)
GMENTS	<u> </u>		BASE METAL		
ATALYST			ALLOYS		
EHICLE			METALLIC COATINGS		
OLVENTS			FILLER METAL PLUS COATINGS OR CORE FLUX		
DDITIVES			OTHERS		
THERS				į	
HAZADARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES					TLV (Units)
ODORLESS MINERAL SPIRITS Less than			10	500	
1,1,1-TRICHLOROETHANE			Less than	25	350

	SECTION III	- PHYSICAL DATA	
BOILING POINT (°F.)	165*	SPECIFIC GRAVITY (H20=1)	> 1
VAPOR PRESSURE (mm Hg.)	N.D.	PERCENT, VOLATILE BY VOLUME (%)	> 25%
VAPOR DENSITY (AIR=1)	>1	EVAPORATION RATE (ether=1)	> 1
SOLUBILITY IN WATER	negligil	ole .	

\*FOR COMPONENT WITH LOWEST VALUE. 120° F

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)
170° F closed cup method

EXTINGUISHING MEDIA

CARBON DIOXIDE, FOAM, DRY CHEMICALS.

SPECIAL FIRE FIGHTING PROCEDURES

NONE

UNUSUAL FIRE AND EXPOLSION HAZARDS

THERMAL DECOMPOSITION CAN FORM TOXIC AND HAZARDOUS GASSES.

SECTION V - HEALTH HAZARD DATA
THRESHOLD LIMIT VALUE
NONE ESTABLISHED BY OSHA.
EFFECTS OF OVEREXPOSURE
MAY CAUSE CNS DEPRESSION, HEADACHE, DIZZINESS, LOSS OF APPETITE, WEAKNESS, LOSS OF
COORDINATION. ASPIRATION OF LIQUID CAN LEAD TO CHEMICAL PNEUMONIA.
EMERGENCY AND FIRST AID PROCEDURES
EYE CONTACT: FLUSH EYES WITH WATER. SKIN CONTACT: FLUSH SKIN WITH SOAP AND WATER.
IF SWALLOWED, DO NOT INDUCE VOMITING. CALL A PHYSICIAN.

the transfer of the second		SECTI	ON VI-F	REACTIVITY DA	ATA	H 0 0 **	<b>-</b>	
STABILITY	UNSTABLE		CONDITIONS TO AVOID			S -	II p sugg brea pric	kno
	STABLE	X			<u></u>	<b>583</b>	pos pos gges gges	4 E
	Y (Materials to avoid)				;	CHAN CHAN IMED	tio of of	ledge. The
HAZARDOUS DEC	OMPOSITION PROD	STRONG OX		AGENTS.		<u></u>	ble ons	1:"
STRONG OXIDIZING A HAZARDOUS DECOMPOSITION PRODUCTS CO2 and CO		CONDITIONS TO	CONDITIONS TO AVOID		T P F E	The		
HAZARDOUS	MAY OC	CUR		COMDITIONS TO	AVOID	TO THE	made we s prior crant mate	1
POLYMERIZATION	WILL NO	T OCCUR	Х			VER VER	wi to to	60
		-				TON	neg u neg	recommend
						(C 13 10 10		end
				OR LEAK PROC	CEDURES	TAL CHO	gu hat O gen	ati
STOP SPIL	EN IN CASE MATER L AT SOURCE.	IAL IS RELEAS	ED OR SPIL	DIKE ETC		CHAM OR SS F		ons
	SALVAGE TANK		JI I DI	DIRE, EIC.		HAMPION' OR IMPLI S FOR A ICE, INC	ante ou e res	10
		•				PION'S IMPLIE OR A P.	exami espons	
WASTE DISPOSAL	METHOD					S H d	ih is it is	negesti
	CINERATION WI	TH OFF-GAS	S SCRUBB	ING. LANDFILL		CHDIC , AND ARTICU	reprene the ibiliterwise	6 6
			· · · · · · · · · · · · · · · · · · ·			DIC AND ICUI	he tt	Þ
				·		AL AR	sen se fs	9 0
- 12.00						P Z	H H G G	Con
DESTUBATORY OF			SPECIAL F	PROTECTION IN	IFORMATION	IMP I	tion com cla	t de
RESPIRATORY PR	OTECTION (Specify RS NOT NEEDED	rype)   IF ADEQUA	TE VENT	LATION IS AVA	ILABLE.	AK IE SE	as end ims	est ine
VENTILATION	LOCAL EXHAU	ST		E VAPOR CONCE	COFOLAL	D [0	r a	to p
	MECHANICAL	General)		- VIII ON CONCI	OTHER	S NO WARRAN	to retions arisi	nou
PROTECTIVE GLO	VES.			EYEPROTECTION	OTHER SAFETY GLAS	EREB SSES.B		H
OTHER PROTECTIV	the state of the s	·			SAFETY GLA	. 4 []		1
						S	ts.	
		OFOTION					(0)	
PRECAUTIONS TO	BE TAKEN IN HAN	LING AND STO	I IX - SPE	CIAL PRECAUT	IONS			
AVOID BREA	ATHING VAPOR.	AVOID CO	NTACT WI	TH EYES AND P	ROLONGED CO	TACT WITH S	SKIN.	
	R FATAL IF SW	ALLOWED.						
OTHER PRECAUTI	UNS DUCE VONTETNO	CATTA	PHYSTOTA	N IMMEDIATELY				_